

Coolspool 29

28V AIRCRAFT START UNIT

The Coolspool 29 is available in two nominal output voltages, 26V DC or 28V DC. This aircraft start unit is used extensively on larger twin turbine aircraft and helicopters where additional amp/hour capacity is required to maintain voltage under load.

Upper Fadc limits vary according to the manufacturer's software and for this reason two versions of the Coolspool 29 are available.

When compared to a 24V DC start unit of the same capacity, the Coolspool 29 delivers a significantly higher performance, resulting in faster spool-ups and cooler starts impacting directly on turbine life.

This aircraft start unit is designed to be carried on board for emergency power or turbine starting and is fitted with an automatic 3-stage internal charger for maximum cell longevity.

The Coolspool 29 is fitted with solid state voltmeter with 'push to view' button to monitor battery voltage.

A spring-loaded output cover ensures the aircraft start unit is cleared for air transportation. Supplied with Nato lead set, charge lead and heavy-duty canvas protective jacket.

Supplied as standard with



Country-specific
input cord



2m (6ft) Nato lead



Padded
protective jacket



Typical power plant:*

Williams FJ-33, PT6-67, Arrius, or power plants of a similar specification



Corporate jets



10-16-seat helicopters with shaft turbines

Coolspool 29

Specifications

Peak amps**	2400A
Nominal voltage	26V or 28V DC depending on model
Standing voltage	27.8V or 30V DC depending on model
Amp/hour capacity	26 Ah @ 10 hr rate (20°C)
Operating temp	-40°C to +45°C. (-22°F to +113°F)
Case	Aluminium with shock absorbing feet
Voltmeter	Solid state LED, IP65
Aircraft cable	2m (6ft) with heavy-duty rubber Nato connector
Charger	1.9A 3-stage internal charger/ 90-264V AC/47-63Hz/single phase
Dimensions	H 345mm (13in), L 405mm (16in), W 135mm (5in)
Weight	26V DC: 28kg (61lb) 28V DC: 29kg (63lb)
NCAGE	KD628

** Peak amps is a theoretical calculation of the instantaneous current from a momentary dead short across the battery terminals. It is not representative of the power delivered at the aircraft plug due to cable losses and other factors. This figure is shown for comparative purposes.

Features

- High powered sealed lead acid AGM batteries
- Cleared for air transportation
- Internal charger with LED status indicator
- Corrosion resistant aluminium case with carry handle
- Controls protected by twin front protection bars
- Aircraft cable with heavy-duty Nato connector
- Spring-loaded output connector cover
- Auxilliary socket for plug-in accessories
- Solid state voltmeter with 'push to view' feature
- Fitted with rubber anti-slip, shock absorbent feet
- Heavy-duty canvas protective jacket

Optional extras



Other ground power units available from AERO Specialties



12/24V GA Pack



GPU 1700



GPU 2400



Coolspool 17



Coolspool 29
Twin



PS100



PS300



AERO Specialties, 11175 W. Emerald St., Boise, ID 83713, USA

Tel: +1 208 378 9888 Fax: +1 208 378 9889 sales@aerospecialties.com www.aerospecialties.com



© Powervamp Ltd. Measurements, weights, technical performance and other specification data are typical and may vary. Powervamp reserves the right to alter or amend specifications without notice as part of its program of continuous improvement. Powervamp is a trademark of Powervamp Ltd.

DMS#3455rev1

