

# TOWER PACK

## 12/24V JUMP START PACK

The Tower Pack is designed primarily for heavy engine starting. The pack is available as a 12V/24V DC dual voltage version. The increased battery capacity is ideal for using within the bus, truck and plant industries for maintenance operations such as fuel bleeding, oil pressure build-up, tail-lift cycling as well as multi engine starting.

The exceptionally tough polyethylene case is shatterproof and is ideal for use in the most demanding of commercial environments. The high 'waistline' enables the pack to be operated in snow or flooded sites up to 300mm, without the risk of water ingress.

The unique design and small overall footprint makes the pack ideal for service vans where space is limited.

The Tower Pack shares many of the safety features associated with Powervamp's premium range of jump starters such as reverse polarity audible warning and voltage spike suppression circuitry for ECU protection. The pack is also fitted with a 750A fused output to protect the battery from a short circuit or excessive cranking.

The standard 2m, 50mm<sup>2</sup> highly flexible output cables allow the operator to safely connect to a flat battery within the engine bay with the pack securely on the ground.

The cables terminate with fully cast 1000A braided croc clips, ensuring an equal power delivery with minimal voltage loss. The cables are detachable to allow for easy storage or replacement.

The Tower Pack is supplied with a 10A external charger and detachable 240V AC power cable.

Optional accessories include bus plug (cowbell) lead sets, a powerful 24V DC inspection lamp, and an on-board charge kit (OBCK) to allow the pack to be charged from a 12V DC vehicle cigarette/auxiliary socket.



### Supplied as standard with



### Typical engines

Petrol engines	up to 7 litres
Diesel engines	up to 14 litres



# TOWER PACK

## Specifications

Peak amps**	2400A
Nominal voltage	12V / 24V DC
Standing voltage	12.8V / 25.6V DC
Amp/hour capacity	26/26Ah @ 10hr rate (20°C)
Fuse rating	750A
Operating temp	-40°C to +45°C (-40°F to +114°F)
Case	Moulded impact resistant polyethylene
Automotive cable	2m (6ft) lead set with 1000A croc clips
Charger	12V, 10A, 100-230V AC / 50-60Hz external charger
Dimensions	H 570mm (22in), L 180mm (7in), W 158mm (6in)
Weight	21kg (55lb)

\*\* Peak amps is a theoretical calculation of the instantaneous current from a momentary dead short across the battery terminals. It is not representative of the power delivered at the croc leads which is significantly less, due to cable losses and other factors. It is a figure of no useful value to the operator and is shown only for comparative purposes.



## Features

- High powered sealed lead acid AGM battery
- 12V, 10A, 3-stage external charger
- 4 LED status display
- 2m (6ft) output lead with 1000A croc clips
- Tough polyethylene case | Audible reverse polarity warning buzzer
- Voltage spike protection PCB
- Switched USB socket for mobile phone / tablet charging
- External 750A fuse output protection
- 12V and 24V DC auxiliary socket for external charging and accessories
- 1000A output key switch isolator

## Optional extras




Trolley



2m cowbell lead



4m cowbell lead



On-board charge kit

## Other jump start packs in the Powervamp range



MR26



TB1224HDD



Nato 200

**Powervamp**<sup>®</sup>  
ADVANCED POWER SOLUTIONS

**Powervamp Ltd** 22 Bridgwater Court, Oldmixon Crescent, Weston-super-Mare, BS24 9AY, England  
Tel: +44 (0)1934 643000 Fax: +44 (0)1934 642800 Email: [info@powervamp.com](mailto:info@powervamp.com) [www.powervamp.com](http://www.powervamp.com)



© Powervamp Ltd. Measurements, weights, technical performance and other specification data are typical and may vary. Powervamp reserves the right to alter or amend specifications without notice as part of its program of continuous improvement. Powervamp is a trademark of Powervamp Ltd.

